

Appl. No. 09/910,604
Reply to Office Action of March 14, 2006

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A solid-state image apparatus comprising:

an image section having a plurality of pixels arranged two dimensionally in the horizontal direction and in the vertical direction,

the image section comprising a first area formed of a first pixel group and a second area formed of a second pixel group, and the first area and the second area being disposed adjacent to each other in the horizontal direction;

a first electric-charge transfer section disposed outside the image area for transferring the signal electric charges of the first area in the horizontal direction;

a second electric-charge transfer section extending across the entire width of the image section and disposed outside the image area for transferring the signal electric charges of the second area in the horizontal direction; and

driving means for driving the first and second electric-charge transfer sections in an identical direction,

wherein the first and second electric-charge transfer sections are disposed such that the first electric-charge transfer section transfers only the signal electric charges of the first area and the second electric-charge transfer section transfers only the signal electric charges of the second area; and

page 2 of 12

Appl. No. 09/910,604
Reply to Office Action of March 14, 2006

further comprising a vertical transfer section for transferring the signal electric charges of the second area to the second electric-charge transfer section without passing through the first electric-charge transfer section,

wherein the first electric-charge transfer section is disposed between the first area and the second electric-charge transfer section, and

wherein the vertical transfer section is disposed between the second area and the second electric-charge transfer section, and

wherein all of the pixels in any one column of said image section to be read out of the solid-state image apparatus are transferred to only one of said first electric-charge transfer section and said second electric-charge transfer section.

2. (Original) A solid-state image apparatus according to Claim 1, wherein the driving means drives the first and second electric-charge transfer sections by an identical driving signal.

3. (Cancelled).

4. (Cancelled)

5. (Currently Amended) A solid-state image device comprising:
an image section having a plurality of pixels arranged two dimensionally in the horizontal direction and in the vertical direction,

Appl. No. 09/910,604
Reply to Office Action of March 14, 2006

the image section comprising a first area formed of a first pixel group and a second area formed of a second pixel group, and the first area and the second area being disposed adjacent to each other in the horizontal direction;

a first electric-charge transfer section disposed outside the image area for transferring the signal electric charges of the first area in the horizontal direction;

a second electric-charge transfer section extending across the entire width of the image section and disposed outside the image area for transferring the signal electric charges of the second area in the horizontal direction; and

a vertical transfer section for transferring the signal electric charges of the second area to the second electric-charge transfer section,

wherein the first electric-charge transfer section is disposed between the first area and the second electric-charge transfer section, and

the vertical transfer section is disposed between the second area and the second electric-charge transfer section, and

wherein all of the pixels in any one column of said image section to be read out of the solid-state image apparatus are transferred to only one of said first electric-charge transfer section and said second electric-charge transfer section.

6. (Currently Amended) A driving method for a solid-state image device, the solid-state image device having: an image section having a plurality of pixels arranged two dimensionally in the horizontal direction and in the vertical direction, the image section having a first area formed of a first pixel group and a second area formed of a second pixel

Appl. No. 09/910,604
Reply to Office Action of March 14, 2006

group, and the first area and the second area being disposed adjacent to each other in the horizontal direction; a first electric-charge transfer section disposed outside the image area for transferring the signal electric charges of the first area in the horizontal direction; and a second electric-charge transfer section extending across the entire width of the image section and disposed outside the image area for transferring the signal electric charges of the second area in the horizontal direction, the driving method comprising:

a step of transferring the signal electric charges of the first area to the first electric-charge transfer section;

a step of transferring the signal electric charges of the second area to the second electric-charge transfer section without passing through the first electric-charge transfer section; and

a step of driving the first and second electric-charge transfer sections in an identical direction to output signal charges; and

further comprising transferring the signal electric charges of the second area to the second electric-charge transfer section without passing through the first electric-charge transfer section via a vertical transfer section thereby transferring the signal electric charges of the second area to the second electric-charge transfer section without passing through the first electric-charge transfer section,

wherein the first electric-charge transfer section is disposed between the first area and the second electric-charge transfer section, and

wherein the vertical transfer section is disposed between the second area and the second electric-charge transfer section, and

Appl. No. 09/910,604
Reply to Office Action of March 14, 2006

wherein all of the pixels in any one column of said image section to be read out of the solid-state image apparatus are transferred to only one of said first electric-charge transfer section and said second electric-charge transfer section.

7. (Currently Amended) A camera system comprising:

a solid-state image apparatus,

the solid-state image apparatus comprising:

an image section comprising a plurality of pixels arranged two dimensionally in the horizontal direction and in the vertical direction, the image section comprising a first area formed of a first pixel group and a second area formed of a second pixel group, and the first area and the second area being disposed adjacent to each other in the horizontal direction;

a first electric-charge transfer section disposed outside the image area for transferring the signal electric charges of the first area in the horizontal direction;

a second electric-charge transfer section extending across the entire width of the image section and disposed outside the image area for transferring the signal electric charges of the second area in the horizontal direction;

driving means for driving the first and second electric-charge transfer sections in an identical direction; and

a vertical transfer section for transferring the signal electric charges of the second area to the second electric-charge transfer section;

an optical system for guiding incident light to the image section of the solid-state image apparatus; and

Appl. No. 09/910,604
Reply to Office Action of March 14, 2006

a signal processing circuit for combining output signals of the solid-state image apparatus to generate a signal corresponding to signal electric charges of one line in the image section,

wherein the first electric-charge transfer section is disposed between the first area and the second electric-charge transfer section, and

the vertical transfer section is disposed between the second area and the second electric-charge transfer section, and

wherein all of the pixels in any one column of said image section to be read out of the solid-state image apparatus are transferred to only one of said first electric-charge transfer section and said second electric-charge transfer section.

8. (Cancelled).

Please add the following new claim:

9. (New) A solid-state image apparatus comprising:

an image section having a plurality of pixels arranged two dimensionally in the horizontal direction and in the vertical direction,

the image section comprising a first area formed of a first pixel group and a second area formed of a second pixel group, and the first area and the second area being disposed adjacent to each other in the horizontal direction;

Appl. No. 09/910,604
Reply to Office Action of March 14, 2006

a first electric-charge transfer section disposed outside the image area for transferring the signal electric charges of the first area in the horizontal direction;

a second electric-charge transfer section extending across the entire width of the image section and disposed outside the image area for transferring the signal electric charges of the second area in the horizontal direction; and

driving means for driving the first and second electric-charge transfer sections in an identical direction,

wherein the first and second electric-charge transfer sections are disposed such that the first electric-charge transfer section transfers only the signal electric charges of the first area and the second electric-charge transfer section transfers only the signal electric charges of the second area; and

further comprising a vertical transfer section for transferring the signal electric charges of the second area to the second electric-charge transfer section without passing through the first electric-charge transfer section,

wherein the first electric-charge transfer section is disposed between the first area and the second electric-charge transfer section, and

wherein the vertical transfer section is disposed between the second area and the second electric-charge transfer section, and

wherein the electric charges of said first area are transferred directly from said first area to said first electric-charge transfer section without passing through any additional vertical transfer section between the first image area and the first electric-charge transfer section.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.